



## HM 1000



- **Hanging module with rugged thread connection and self-cleaning, gold plated contacts**
- **For use with five different Capsule Modules**
- **Integrated switchable LED ring**
- **Integrated bass rolloff filter**
- **Rugged all-metal construction**
- **Non-reflective anthracite finish**

Using microphones flown from the ceiling to record music or speech in places of worship, conference rooms, or on theater stages is becoming more and more popular.

A 10-m (33-ft.) special cable that is treated specially to reduce twisting to a minimum even if the temperature varies and a spring steel hanging clamp for precise microphone alignment will keep the microphone securely in its position.

See [mounting example](#)

A switchable LED ring helps the sound engineer to check system function during the soundcheck.

Available capsule modules for HM 1000: CK 31, CK 32, CK 33, CK 47, CK 80.

## Specifications

<b>Bass filter</b>	250 Hz, -10 dB at 50 Hz
<b>Impedance</b>	$\leq 600$ ohms
<b>Recommended load impedance</b>	$\geq 2,000$ ohms
<b>Supply voltage</b>	9 to 52 V phantom power to DIN/IEC
<b>Current consumption</b>	$< 2$ mA
<b>Connector</b>	3-pin male XLR

<b>Cable</b>	10 m (33 ft.)
<b>Finish</b>	matte dark grey
<b>Dimensions</b>	13.5 dia. x 50 length mm (0.5 dia. x 2.0 length in.)
<b>Net weight</b>	400 g (14.1 oz.)
<b>Shipping weight</b>	600 g (1.3 lbs.)