

Key Features:

- ▶ Robust 15mm enclosure with black textured finish
- ▶ 381 mm (15 in) LF transducer
- ▶ 60° x 60° Waveguide with a 25 mm (1 in) exit 38mm (1.5") diaphragm compression driver
- ▶ Dual Neutrik NL4 connectors plus screw terminals
- ▶ Multiple attachment points for ultimate flexibility

Applications:

- ▶ Performing Spaces
- ▶ Clubs & Bars
- ▶ Houses of Worship
- ▶ Multi Media Spaces
- ▶ Retail & Hospitality Spaces
- ▶ Presentation Suites
- ▶ Educational Facilities

AC566 is a compact 2-way full-range loudspeaker system comprised of one 381 mm (15 in) low frequency driver and one 25 mm (1 in) exit/38 mm (1.5 in) voice-coil compression driver. The horn provides 60° by 60° coverage in vertical and horizontal orientation. High-slope passive crossovers minimize band overlap and well-controlled offaxis response.

The cabinet is fitted with M10 threaded suspension points. Four threaded inserts located on back of the enclosure allow attachment of a MultiMount® or similar type mounting.

AC566 is part of JBL's AE Application Engineered Series, a versatile family of loudspeakers for a wide variety of fixed installation applications.



Specifications:

| | |
|--|---|
| System: | |
| Frequency Range (-10 dB) ¹ : | 60 Hz - 20 kHz |
| Frequency Response (±3 dB) ¹ : | 75 Hz - 18kHz |
| System Sensitivity (1w @ 1m) ¹ : | 98 dB |
| Nominal Impedance: | 8 ohms |
| Maximum SPL(1m) ² : | 123 dB (129 dB peak) |
| Power Rating ³ : (Continuous/Program/Peak) | 300 W/600 W/1200 W |
| Coverage Pattern: | 60° x 60° (H x V) |
| Crossover: | 1.5 kHz |
| Transducers: | |
| Low frequency driver: | 1 x 15" woofer (P/N: 5053935), 381 mm (15 in) driver with 38 mm (1.5 in) voice-coil |
| High frequency driver: | 1 x 2408H-2 driver with 25 mm (1 in) exit/38 mm (1.5 in) voice-coil |
| Physical: | |
| Input Connector: | Dual Neutrik NL4MP connectors plus covered barrier trip terminals |
| Enclosure: | 15 mm multi-ply hardwood plywood |
| Grille: | Powder coated, 1.5mm perforated steel, with acoustically transparent black foam backing |
| Finish: | Textured black paint finish. White (-WH) available upon request. Not available with WRC & WRX finish. |
| Suspension / Mounting: | 14 x M10 and 4 x M10 for Wall Mount Bracket. Optional U-bracket, L-bracket and wall-mount bracket |
| Dimensions (H x W x D): | 680 mm x 420 mm x 445 mm 26.7 in x 16.5 in x 17.5 in |
| Net Weight: | 19.8 kg (43.6lbs) |

1 Full space (4π) conditions

2 Calculated maximum SPL based on rated power handling

3. IEC shaped pink noise with 6dB CF for 100hrs

JBL continually engages in research related to product improvement. Some materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.

