



# CSS8004

Commercial Series Ceiling Speaker

# INSTALLATION INSTRUCTIONS

1. Install according to diagram.
2. Connect leads according to Tap Wiring chart.
3. Cut off bare portion of unused leads and terminate with wire nuts.

Note: Always install in accordance with applicable electrical and building codes.

### Tap Wiring:

	Orange	Green	Gray	Yellow	Black
<b>25V</b>	0.7W	1.3W	2.5W	5W	COM

	White	Blue	Brown	Orange	Black
<b>70V</b>	0.7W	1.3W	2.5W	5W	COM
<b>100V</b>	1.3W	2.5W	5W	N/C	COM



JBL Professional  
8500 Balboa Boulevard, P.O. Box 2200  
Northridge, California 91329 U.S.A.


### Tile Rails CSS-TR4/8 (x2)

Secure rails to ceiling/grids in manner required by local building code.



### Back Can CSS-BB4

Back Can / Tile Rail screws (machine screws) M4 x 8 mm (4 places, packaged with back can)




Install screw through thru-hole in back can, and screw into tile rail.

Ceiling Material

### CSS8004 Speaker

Speaker screws (sheet metal screws) M4 x 40 mm (4 places, packaged with speaker)



Install screw through thru-hole in speaker, screw into clip nut in back can.