PRODUCT SPECIFICATION 1/2



# MD 445 Vocal Microphone



The top model of dynamic Sennheiser microphones sounds impressive thanks to its unparalleled presence and openness.

The sophisticated and extensive sound calibration of the dynamic, wired microphone creates noticeably greater proximity to the vocals. With its high-rejection supercardioid pickup pattern, the MD 445 provides focus in every application and systematically protects against feedback – even at extreme volumes. Thanks to its rugged metal design, it can withstand extensive wear and tear.

#### **FEATURES**

- · Dynamic vocal microphone
- Very lightweight, rapidly responding aluminum- copper voice coil
- High-resolution, direct sound for audibly greater proximity to the vocals
- · Directionality: high-rejection supercardioid
- · Extremely high feedback resistance
- Large diaphragm diameter
- Spring-mounted capsule to shield it from body-borne noise
- Hum compensation coil to eliminate electromagnetic interference
- Rugged metal design



#### **ARTICLE INFORMATION**

| MD 445 | Art. no. 508828 |
|--------|-----------------|
|        |                 |

#### **ACCESSORIES**

| MD 445 Basket Black   | Art. no. 509205 |
|-----------------------|-----------------|
| MD 445 Pop Protection | Art. no. 509207 |


## **SPECIFICATIONS**

| Transducer principle                  | dynamic                         |
|---------------------------------------|---------------------------------|
| Frequency response                    | 40 – 20,000 Hz                  |
| Pick-up pattern                       | high rejection<br>supercardioid |
| Sensitivity<br>(free field, at 1 kHz) | 1.6 mV/Pa<br>-55.9 dBV/Pa       |
| Max SPL at 1 kHz                      | 163 dB                          |
| Equivalent noise level                | 18 dB(A)                        |
| Dynamic range                         | 145 dB(A)                       |
| Nominal impedance<br>(at 1 kHz)       | 245 Ω                           |
| Min. terminating impedance            | 1 kΩ                            |
| Connector                             | XLR-3M                          |
| Dimensions                            | Ø 47.5 x 174 mm                 |
| Weight                                | 329 g                           |
|                                       |                                 |



# MD 445 Vocal Microphone

## **POLAR PATTERN**



# **FREQUENCY RESPONSE**

